

NAV-Z Applicable pipe list in case of **A**

Butterfly Valves	Nominal size		SGP	Sch20	Sch40	VP (TS flange)	Sch10S	Sch20S	Minimum internal diameter of piping (mm)
	mm	inch							
TRITEC	40	1 1/2		-					25
TT2	50	2							34
334A	65	2 1/2							51
302A/303Q	80	3							70
304A/304Q	100	4							91
302Y/304Y	125	5							118
304M(HLV)	150	6							144
507V/508V	200	8							194
846T/847T/847Q	250	10							246
841T/842T	300	12							294

NAV-Z Applicable pipe list in case of **B**

Butterfly Valves	Nominal size		SGP	Sch20	Sch40	Sch10S	Sch20S
	mm	inch					
700G/704G/705G	40	1 1/2		-			
731P/732P 732X/731X	50	2					
700E/700K	65	2 1/2					
704G/722F/720F	80	3					
LRV	100	4					
227P	125	5					
MKT	150	6					
903C/904C	200	8					
	250	10					
	300	12					

Remark 1: = Applicable

Remark 2: Butterfly valves are inserted into a pipe that was fitted with the disc when fully open.

In cases where you are using a pipe or flange that is less than the minimum inner pipe diameter, use is still possible if means are taken such as inserting a spacer between the valve and flange. For details, please consult us.

